

Ev Charger Wall Mount 7kw

Production Parameters		
Model	7KW	
AC Input	Input Rating	220Vac $\pm$ 10%
	AC Input Connection	L2+L3+PE (NEMA,JPS)
	Max. Input Current	32A
	Frequency	50 /60 Hz
	Power Factor	>0.99@full load
	Efficiency	95%
DC Output	Output Voltage Range	200-750Vdc
	Max. Output Power	7KW
	Max. Output Current	20A
User Interface	TFT-LCD Touch Panel	No
	Push Buttons	No
	Interface	USB
Packing	Dimension	410 $\times$ 149 $\times$ 250mm
	Weight	20KG
Environmental	Operating Temperature	-40~85℃, 25℃ (TYPE)
	Humidity	5%-90% RH, non-condens,ng
	Altitude	2000m
	IP Level	IP43

Add: 1st Floor, 88 Building, Xiameilin,Futian Area,ShenZhen,Guangdong,China. 518052
Tel/Wechat/Whatsapp: +8617326560631 Email: guangyuan.z@foxmail.com

Mechanical	Cable Length	5M (CHAdEMO) , 5M (CCS), 5M(GB/T) Customized acceptable
	Regulation	EN61851-1
Regulation	Certification	CE , ROHS
	Charging protocol	CHAdEMO 2.0 / DIN 70121/ISD1S118/IEC61851- 23,IEC61851-24