

Ev Charger Wall Mount 40kw

Model		40KW
AC Input	Input Rating	380Vac $\pm$ 10%
	AC Input Connection	3P + N +PE, Wye connection
	Max. Input Current	80A
	Frequency	50 /60 Hz
	Power Factor	>0.99@full load
	Efficiency	95%
DC Output	Output Voltage Range	200-750Vdc
	Max. Output Power	40KW
	Max. Output Current	120A
User Interface	TFT-LCD Touch Panel	Yes(swiping card without TFT-LCD Touch Panel)
	Push Buttons	Yes
	Interface	Yes
Packing	Dimension	W:548 $\times$ 378 $\times$ 250mm U:1500 $\times$ 520 $\times$ 250mm
	Weight	Wall:45KG Upright:50KG
Environmental	Operating Temperature	-40~85℃, 25℃ (TYPE)
	Humidity	5%-90% RH, non-condens,ng
	Altitude	2000m
	IP Level	IP54
Mechanical	Cable Length	5M (CHAdMO) , 5M (CCS), 5M(GB/T) Customized acceptable
	Regulation	EN61851-1
Regulation	Certification	CE , ROHS
	Charging protocol	CHAdMO 2.0 / DIN 70121/ISD1S118/IEC61851-

Add: 1st Floor, 88 Building, Xiameilin, Futian Area, ShenZhen, Guangdong, China. 518052
Tel/Wechat/Whatsapp: +8617326560631 Email: guangyuan.z@foxmail.com

	23,IEC618S1-24
--	----------------